

6' WIDE SA PRO SERIES

| 6' Wide SA Standard Specifications | | | | | |
|------------------------------------|----------------|----------------|----------------|----------------|--|
| | 6 x 8 SA | 6 x 10 SA | 6 x 12 SA | 6 x 14 SA | |
| Overall Length | 12' 5" | 14' 5" | 16' 5" | 18' 5" | |
| Width | 93" | 93" | 93" | 93" | |
| Height | 87" | 87" | 87" | 87" | |
| Interior Length | 8' 8" | 10' 8" | 12' 8" | 14' 8" | |
| Width | 69 1/2" | 69 1/2" | 69 1/2" | 69 1/2" | |
| Height | 66" | 66" | 66" | 66" | |
| Platform Height | 19" | 19" | 19" | 19" | |
| Axes | Torsion | Torsion | Torsion | Torsion | |
| Brakes | Optional | Optional | Optional | Optional | |
| Frame | 2" x 4" | 2" x 4" | 2" x 4" | 2" x 4" | |
| Tire Size | ST225/75D15 | ST225/75D15 | ST225/75D15 | ST225/75D15 | |
| Hitch Ball Size | 2" | 2" | 2" | 2" | |
| Curb Weight (#) | 1100 | 1220 | 1340 | 1460 | |
| Hitch Weight (#) | 110 | 150 | 200 | 250 | |
| GVWR (#) | 2990 | 2990 | 2990 | 2990 | |
| Payload Capacity (#) | 1890 | 1770 | 1650 | 1530 | |
| Rear Doors | Double | Double | Double | Double | |
| Opening Width | 62" | 62" | 62" | 62" | |
| Opening Height | 59 1/2" | 59 1/2" | 59 1/2" | 59 1/2" | |
| Exterior | .030 Smooth | .030 Smooth | .030 Smooth | .030 Smooth | |
| Floor (24" O.C.) | 3/4" Advantech | 3/4" Advantech | 3/4" Advantech | 3/4" Advantech | |
| Sidewalls (16" O.C.) | 3/16" Luan | 3/16" Luan | 3/16" Luan | 3/16" Luan | |

00-9006 6X SA Standard Features

- 2" X 4" Welded Tubular Steel Main Frame
- 2" Coupler With A-Frame
- 3500# Dexter Torsion Axle With E-Z Lube Hubs
- ST225/75D15 LRC Tires
- 4 Way Flat Electrical Plug
- 3/4" Advantech Floor (24" O/C)
- 3/16" Luan Plywood Walls (16" O/C)
- .030 Smooth Aluminum Exterior
- Painted Aluminum Rear Header
- Round Top With Fiberglass Front Cap
- Seamless Aluminum Roof And Radius Wrap
- Brushed Aluminum Fenders
- 24" Gravel Guard With Bottom Trim
- 32" Curbside Door With Bar Lock
- Double Rear Doors With Cam Lock
- Zinc Coated Door Hardware
- 12 Volt Dome Light With Wall Switch
- DOT Approved Lighting and Safety Equipment
- Limited 5 Year Warranty

6' WIDE XL

| 6' Wide XL Standard Specifications | | | | | |
|------------------------------------|----------------|----------------|----------------|----------------|--|
| | 6 X 8XL | 6 X 10XL | 6 X 12XL | 6 X 12XL2 | |
| Overall Length | 12' 5" | 14' 5" | 16' 5" | 16' 5" | |
| Width | 92" | 92" | 92" | 92" | |
| Height | 86" | 86" | 86" | 92" | |
| Interior Length | 8' 7" | 10' 7" | 12' 7" | 12' 7" | |
| Width | 69 1/2" | 69 1/2" | 69 1/2" | 69 1/2" | |
| Height | 66" | 66" | 66" | 72" | |
| Platform Height | 17" | 17" | 17" | 17" | |
| Axles | Spring | Spring | Spring | Spring | |
| Brakes | Optional | Optional | Optional | Electric | |
| Frame | 2" X 3" | 2" X 3" | 2" X 3" | 2" X 3" | |
| Tire Size | ST205/75D15 | ST205/75D15 | ST205/75D15 | ST205/75D15 | |
| Hitch Ball Size | 2" | 2" | 2" | 2 5/16" | |
| Curb Weight (#) | 1100 | 1200 | 1300 | 1570 | |
| Hitch Weight (#) | 110 | 120 | 130 | 160 | |
| GVWR (#) | 2990 | 2990 | 2990 | 7000 | |
| Payload Capacity (#) | 1890 | 1790 | 1690 | 5430 | |
| Rear Doors | Double | Double | Double | Double | |
| Opening Width | 62" | 62" | 62" | 62" | |
| Opening Height | 59 1/2" | 59 1/2" | 59 1/2" | 65 1/2" | |
| Opening Height w/ Beaver | N/A | N/A | N/A | N/A | |
| Exterior | .030 Smooth | .030 Smooth | .030 Smooth | .030 Smooth | |
| Floor (24" O.C.) | 3/4" Advantech | 3/4" Advantech | 3/4" Advantech | 3/4" Advantech | |
| Sidewalls (24" O.C.) | 3/16" Luan | 3/16" Luan | 3/16" Luan | 3/16" Luan | |

00-9020 Standard Features

- 2" X 3" Welded Tubular Steel Main Frame
- 2" Coupler With A-Frame, 2 5/16" On TA
- 3500# Spring Axle(s) With 4" Drop
- ST205/75D15 LRC Tires for XL
- 4 Way Electric Brakes On TA
- Gel Cell Rechargeable Breakaway Kit On TA
- 4 Way Flat Electrical Plug, 7 Way On TA
- 3/4" Advantech Floor (24" O/C)
- 3/16" Luan Plywood Walls (24" O/C)
- .030 Smooth Aluminum Exterior
- Exterior Screwed 24" On Centers
- Painted Aluminum Rear Header
- Round Top With Fiberglass Front Cap (Black Or White)
- Galvalume Roof
- Brushed Aluminum Fenders
- 24" Gravel Guard With Bottom Trim
- 32" Curbside Door With Bar Lock
- Double Rear Doors With Cam Lock
- Zinc Coated Door Hardware
- 12 Volt Dome Light With Wall Switch
- DOT Approved Lighting and Safety Equipment
- Limited 3 Year Warranty

CONFIDENTIAL